

G182 RSD® Product Sheet



FEATURES	BENEFITS
Innovative tread compound	Helps deliver long miles to removal in demanding drive applications
Deep 28/32" open lug tread design	Helps enhance traction while delivering long miles to removal
Enhanced casing with steel belt package	Helps offer toughness and outstanding performance through multiple retread cycles
Mirrored, non-directional tread design	Offers footprint uniformity and even wear.
Tie-Bar Shoulder And Bladed Tread Pattern	Help deliver long, even wear

APPLICATION GUIDELINES

Goodyear's Best Regional Drive Tire for Long Miles to Removal

SIZE	TREAD DEPTH	RIM WIDTH (IN) (MM)	TIRE WEIGHT (LBS) (KG)	OVERALL WIDTH (IN) (MM)	OVERALL DIAMETER (IN) (MM)	STATIC LOADED RADIUS (IN) (MM)	RETREAD BUFFING RADIUS (IN) (MM)	RETREAD BASE WIDTH (IN) (MM)
TUBELESS TIRES ON 15° DROP CENTER RIMS								
11R22.5 G	28	0.00 0	124 56	0.0 0	0.0 0	0.0 0	0 0	0.000 0
11R22.5 H	28	8.25 210	125 57	10.8 274	42.1 1,069	19.6 498	24 610	0.000 0
11R24.5 H	28	8.25 210	138 62	11.0 279	44.1 1,120	20.8 528	22 559	0.000 0
295/75R22.5 G	28	8.25 210	118 54	11.3 287	40.8 1,036	19.0 483	26 660	0.000 0

SIZE	SPEED RATING (MPH)	SINGLE MAX LOAD (LBS) (KG)	SINGLE INFLATION (PSI) (KPa)	DUAL MAX LOAD (LBS) (KG)	DUAL INFLATION (PSI) (KPa)	REVS PER (MILE) (KM)	MINIMUM DUAL SPACING (IN) (MM)	PRODUCT CODE
TUBELESS TIRES ON 15° DROP CENTER RIMS								
11R22.5 G	0	6,175 2,800	105 720	5,840 2,650	105 720	0 0	0.0 0	138802111
11R22.5 H	75	6,610 3,000	120 830	6,005 2,725	120 830	496 308	12.5 318	138803185
11R24.5 H	75	7,160 3,250	120 830	6,610 3,000	120 830	473 294	12.5 318	138941185
295/75R22.5 G	75	6,175 2,800	110 760	5,675 2,575	100 690	512 318	12.9 328	756817111