

G751® MSA™ Duraseal™ Product Sheet



FEATURES

Higher-scrub tread compound and more wearable rubber

Deep 24/32" tread depth with more wearable rubber volume

Enhanced casing with steel belt package

Wider footprint

Built-in DuraSeal Technology

BENEFITS

Help resist cuts, chips and tears and offers long miles to removal in on and off the road applications

Helps put more wearable rubber on the road for enhanced mileage.

Helps offer toughness and outstanding performance through multiple retread cycles

Helps improve stability and traction

Helps seal tread punctures and reduce downtime. *Seals up to 1/4" diameter punctures only in the repairable area of the tread. Does not seal sidewall punctures.

APPLICATION GUIDELINES

Goodyear's Best Mixed Service All-Position Tire for Long Miles to Removal in On-and Off-road Applications with Puncture Sealing Technology

SIZE	TREAD DEPTH	RIM WIDTH		TIRE WEIGHT		OVERALL WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		RETREAD BUFFING RADIUS		RETREAD BASE WIDTH	
		(IN)	(MM)	(LBS)	(KG)	(IN)	(MM)	(IN)	(MM)	(IN)	(MM)	(IN)	(MM)	(IN)	(MM)
TUBELESS TIRES ON 15° DROP CENTER RIMS															
11R22.5 H	24	8.25	210	144	65	11.0	279	42.0	1,067	19.6	498	0	0	0.000	0

SIZE	SPEED RATING (MPH)	SINGLE MAX LOAD (LBS) (KG)	SINGLE INFLATION (PSI) (KPa)	DUAL MAX LOAD (LBS) (KG)	DUAL INFLATION (PSI) (KPa)	REVS PER (MILE) (KM)	MINIMUM DUAL SPACING (IN) (MM)	PRODUCT CODE
TUBELESS TIRES ON 15° DROP CENTER RIMS								
11R22.5 H	68	6,610 3,000	120 830	6,005 2,725	120 830	497 309	12.5 318	138799577