

G278 MSD® Product Sheet



FEATURES	BENEFITS
Severe service tread compound	Helps resist cuts, chips and tears and offers enhanced mileage.
Deep 30/32" open shoulder tread design	Helps provide traction in wet and snowy conditions while delivering long miles to removal
Enhanced casing with steel belt package	Helps offer toughness and outstanding performance through multiple retread cycles
Rugged tread blocks	Help provide excellent off-road traction.

APPLICATION GUIDELINES

Goodyear's Best Mixed Service Super Single Drive Tire for Long Miles to Removal and Traction in Severe Applications

SIZE	TREAD DEPTH	RIM WIDTH (IN) (MM)	TIRE WEIGHT (LBS) (KG)	OVERALL WIDTH (IN) (MM)	OVERALL DIAMETER (IN) (MM)	STATIC LOADED RADIUS (IN) (MM)	RETREAD BUFFING RADIUS (IN) (MM)	RETREAD BASE WIDTH (IN) (MM)
TUBELESS TIRES ON 15° DROP CENTER RIMS								
385/65R22.5 J	30	11.75 298	181 82	14.8 376	43.0 1,092	19.9 505	42 1067	0.000 0
425/65R22.5 L	30	12.25 311	201 91	16.5 419	44.6 1,133	20.5 521	32 813	0.000 0
445/65R22.5 L	30	13.00 330	221 100	18.0 457	46.0 1,168	21.1 536	36 914	0.000 0

SIZE	SPEED RATING (MPH)	SINGLE MAX LOAD		SINGLE INFLATION		DUAL MAX LOAD		DUAL INFLATION		REVS PER		MINIMUM DUAL SPACING		PRODUCT CODE
		(LBS)	(KG)	(PSI)	(KPa)	(LBS)	(KG)	(PSI)	(KPa)	(MILE)	(KM)	(IN)	(MM)	
TUBELESS TIRES ON 15° DROP CENTER RIMS														
385/65R22.5 J	68	9,370	4,250	120	830	0	0	0	0	485	301	0.0	0	756513422
425/65R22.5 L	68	11,400	5,150	0	0	0	0	830	120	468	291	0.0	0	756514422
445/65R22.5 L	68	12,300	5,600	120	0	5,600	0	830	120	453	282	0.0	0	756515422