

Product Sheet



FEATURES

BENEFITS

APPLICATION GUIDELINES

| SIZE | TREAD<br>DEPTH | RIM<br>WIDTH |      | TIRE<br>WEIGHT |      | OVERALL<br>WIDTH |      | OVERALL<br>DIAMETER |      | STATIC LOADED<br>RADIUS |      | RETREAD<br>BUFFING RADIUS |      | RETREAD<br>BASE WIDTH |      |
|------|----------------|--------------|------|----------------|------|------------------|------|---------------------|------|-------------------------|------|---------------------------|------|-----------------------|------|
|      |                | (IN)         | (MM) | (LBS)          | (KG) | (IN)             | (MM) | (IN)                | (MM) | (IN)                    | (MM) | (IN)                      | (MM) | (IN)                  | (MM) |

| SIZE | SPEED<br>RATING<br>(MPH) | SINGLE MAX<br>LOAD<br>(LBS) (KG) | SINGLE<br>INFLATION<br>(PSI) (KPa) | DUAL MAX<br>LOAD<br>(LBS) (KG) | DUAL<br>INFLATION<br>(PSI) (KPa) | REVS<br>PER<br>(MILE) (KM) | MINIMUM<br>DUAL SPACING<br>(IN) (MM) | PRODUCT<br>CODE |
|------|--------------------------|----------------------------------|------------------------------------|--------------------------------|----------------------------------|----------------------------|--------------------------------------|-----------------|
|------|--------------------------|----------------------------------|------------------------------------|--------------------------------|----------------------------------|----------------------------|--------------------------------------|-----------------|